NSN 6625-00-807-3465

Audio Level Meter - Page 1 of 2

Moving iron vane



View Online at https://aerobasegroup.com/nsn/6625-00-807-3465

| Circuit Current For Which Designed: |
|---|
| Ac |
| Dielectric Withstanding Voltage In Volts: |
| 1500.0 |
| Overall Length: |
| 1.437 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.312 inches |
| Overall Height: |
| 1.758 inches |
| Overall Width: |
| 1.758 inches |
| Mounting Hole Diameter: |
| 0.125 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Furnished Items And Quantity: |
| Nut 6; washer 6 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Frequency Response Range: |
| +0.025/+10.000 kilohertz |
| Sensitivity Rating: |
| 1.0 milliwatts |
| Dial Scale Marking Color: |
| White single indicator single range |
| Accuracy In Percent: |
| -3.0/+3.0 at full scale single indicator single range |
| Unable To Decode: |
| Unable to decode or unable to decode |
| Meter Depth Behind Mounting Flange: |
| 0.853 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.510 inches |
| 1.510 littles |

NSN 6625-00-807-3465 Audio Level Meter - Page 2 of 2



| Background Color: |
|--|
| Black single indicator single range |
| Pointer Color: |
| White single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 4 screw and 4 unthreaded hole |
| Scale Graduation Type: |
| Nonlinear single indicator single range |
| Measurement Range: |
| -12.0/+22.0 decibels single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 solder lug and 2 threaded stud |
| Special Features: |
| Ruggedized |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Cadmium and chromate |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |