

View Online at <https://aerobasegroup.com/nsn/6625-00-808-0519>

Circuit Current For Which Designed:

Ac

Overall Length:

2.390 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.040 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.670 inches

Overall Height:

3.940 inches

Overall Width:

4.250 inches

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.650 inches

Furnished Items And Quantity:

Term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+25.000/+125.000 hertz

Sensitivity Rating:

135.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.090 inches

Meter Body Diameter Behind Mounting Flange:

3.250 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+150.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Phase:

Single

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0