

View Online at <https://aerobasegroup.com/nsn/6625-00-809-8083>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.560 inches

Overall Height:

4.220 inches

Overall Width:

4.660 inches

Scale Division Quantity:

40 single indicator single range

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

41.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.790 inches

Meter Body Diameter Behind Mounting Flange:

2.250 inches

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Measurement Range:

-200.0/+200.0 microamperes, dc single indicator single range

Mounting Stud Diameter:

0.138 inches

Circuit Attachment Method And Quantity:

2 threaded stud

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0