

View Online at <https://aerobasegroup.com/nsn/6625-00-810-3950>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.650 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Scale Division Quantity:**

50 single indicator all ranges

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Shock resistant and vibration resistant and water resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Mtg hdw 3; term. Hdw 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Green, apple, phosphorescent single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.600 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator all ranges

**Pointer Color:**

Green, apple, phosphorescent single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+1.0 milliamps single indicator 1st range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

Crystal current ma above scale, reflector voltage-volts below scale

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Radioactive Content:**

Contains radioactive material

**Surface Treatment:**

Enamel semigloss

**Special Test Features:**

Conforms to mil-m-10304/5, type mr26s001dcma

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Coil resistance shall be 100 ohms plus or minus 5 percent at 20 degrees centigrade

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0