NSN 6625-00-810-3950

Multiple Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

Dc



View Online at https://aerobasegroup.com/nsn/6625-00-810-3950

Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
50 single indicator all ranges
Overall Diameter:
2.695 inches
Environmental Protection:
Shock resistant and vibration resistant and water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Mtg hdw 3; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Mounting Arrangement Style: Three hole/stud bolt circle
Three hole/stud bolt circle
Three hole/stud bolt circle Sensitivity Rating:
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color:
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent:
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange:
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.600 inches
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange:
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type:
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet
Three hole/stud bolt circle Sensitivity Rating: 1.0 milliamperes Dial Scale Marking Color: Green, apple, phosphorescent single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color:

External

Power Source:

NSN 6625-00-810-3950Multiple Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
+0.0/+1.0 milliamps single indicator 1st range
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Special Markings:
Crystal current ma above scale, reflector voltage-volts below scale
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Radioactive Content:
Contains radioactive material
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304/5, type mr26s001dcma
Style Designator:
Round flush mtg
Supplementary Features:
Coil resistance shall be 100 ohms plus or minus 5 percent at 20 degrees centigrade
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0