## NSN 6625-00-812-9989

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-812-9989

Circuit	Current	For	Which	Designed:
On our	Ourioni		*****	Doorgiioa.

Ac

**Dielectric Withstanding Voltage In Volts:** 

3000.0

**Overall Length:** 

2.850 inches

**Mounting Hole Diameter:** 

0.150 inches

**Scale Division Quantity:** 

46 single indicator single range

**Overall Diameter:** 

3.510 inches

**Mounting Bolt Circle Diameter:** 

3.160 inches

**Furnished Items And Quantity:** 

Flat washers 4, lockwashers 3, nuts 7, screws 3

**Indicator Type:** 

Dial w/pointer

**Installation Design:** 

Panel

**Mounting Arrangement Style:** 

Three hole/stud bolt circle

**Dial Scale Marking Color:** 

Black single indicator single range

**Accuracy In Percent:** 

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:** 

2.450 inches

**Meter Body Diameter Behind Mounting Flange:** 

2.800 inches

**Movement Type:** 

Moving coil, permanent magnet

**Background Color:** 

White single indicator single range

**Pointer Color:** 

Black single indicator single range

**Mounting Facility Type And Quantity:** 

1 flange and 3 unthreaded hole

**Scale Graduation Type:** 

Linear single indicator single range

**Measurement Range:** 

+0.0/+500.0 milliamperes, dc single indicator single range

## NSN 6625-00-812-9989

Ammeter - Page 2 of 2



Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Caption milliamperes a.C. Center of dial below div scale
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Round flush mtg
Test Data Document:
31349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-m-10304/14 government specification
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A310a0