## NSN 6625-00-814-3854

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-814-3854

| Mounting Type:                                   |  |  |
|--|--|--|
| Mounting Type: Rack                              |  |  |
| Overall Length:                                  |  |  |
| 19.812 inches                                    |  |  |
| Overall Height:                                  |  |  |
| 16.062 inches                                    |  |  |
| Overall Width:                                   |  |  |
| 19.250 inches                                    |  |  |
| Current Type:                                    |  |  |
| Ac   |  |  |
| Frequency Rating:                                |  |  |
| 60.0 hertz                                       |  |  |
| Case Material:                                   |  |  |
| Metal  |  |  |
| Case Surface Treatment:                          |  |  |
| Enameled   |  |  |
| Frequency Range Rating:                          |  |  |
| +4.200/+11.000 gigahertz                         |  |  |
| Internal Battery Accommodation:                  |  |  |
| Not included                                     |  |  |
| Output Impedance Rating:                         |  |  |
| 50.0 ohms  |  |  |
| Voltage Rating:                                  |  |  |
| Between 115.0 volts and 230.0 volts              |  |  |
| Frequency Band Quantity:                         |  |  |
| 1  |  |  |
| Modulation Type:                                 |  |  |
| Pulse  |  |  |
| Calibration Accuracy Rating:                     |  |  |
| Porm 1 pct                                       |  |  |
| Crystal Controlled Feature:                      |  |  |
| Not provided                                     |  |  |
| Calibrated Signal Output Range:                  |  |  |
| 0.1 uv to 0.223 v                                |  |  |
| Signal Output Constancy:                         |  |  |
| Porm 2 db maximum variation throughout frequency |  |  |
| Modulator Location:                              |  |  |
| External   |  |  |
| Modulated Frequency Rating:                      |  |  |
| Between 60.0 hertz and 10.0 kilohertz            |  |  |
| Pulse Repetition Frequency Rating:               |  |  |

Between 10.0 hertz and 10.0 kilohertz

## NSN 6625-00-814-3854

Signal Generator - Page 2 of 2



| Modul | lation | Degree: |
|-------|--------|---------|
|-------|--------|---------|

Between 0.2 usec pulse and 100.0 usec pulse and 0.2 usec pulse and 10.0 usec pulse and 5.0 deviation

Phase:

Single

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T320-j