

View Online at <https://aerobasegroup.com/nsn/6625-00-814-6701>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

250.0

Overall Length:

1.130 inches

Scale Division Quantity:

10 single indicator single range

Overall Diameter:

0.687 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 1; washer 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes and 500.0 ohms

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.810 inches

Meter Body Diameter Behind Mounting Flange:

0.595 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 threaded body and 1 threaded ring

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+1.0 milliamperes, dc single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Wt 1 oz max

Special Markings:

Red dot at pos term.

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Round flush mtg

Supplementary Features:

Int res 500 ohms

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0