NSN 6625-00-814-6837

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-814-6837

Circuit Current For Which Designed: Dc Dielectric Withstanding Voltage In Volts: 2000.0 Overall Length: 2.484 inches Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 10 single indicator single range Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Dielectric Withstanding Voltage In Volts: 2000.0 Overall Length: 2.484 inches Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 10 single indicator single range Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Overall Length: 2.484 inches Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 10 single indicator single range Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Overall Length: 2.484 inches Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 10 single indicator single range Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 10 single indicator single range Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 10 single indicator single range Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
O.125 inches Scale Division Quantity: 10 single indicator single range Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Scale Division Quantity: 10 single indicator single range Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Overall Diameter: 2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
2.695 inches Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Environmental Protection: Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Dust resistant Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Mounting Bolt Circle Diameter: 2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
2.440 inches Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Three hole/stud bolt circle Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Dial Scale Marking Color: White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
White single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.359 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
Black single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range

NSN 6625-00-814-6837 Ammeter - Page 2 of 2



Measurement Range:
+0.0/+1.0 amperes, dc single indicator single range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 binding post
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0