

View Online at <https://aerobasegroup.com/nsn/6625-00-815-0423>

Circuit Current For Which Designed:

Ac

Overall Length:

Between 2.860 inches and 2.890 inches

Mounting Hole Diameter:

Between 0.141 inches and 0.171 inches

Frequency Rating:

60.0 hertz

Overall Diameter:

Between 2.485 inches and 2.515 inches

Mounting Bolt Circle Diameter:

Between 3.172 inches and 3.202 inches

Furnished Items And Quantity:

Mtg hdw 3

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+50.000/+60.000 hertz

Resonant Reed Quantity:

14

Meter Depth Behind Mounting Flange:

2.000 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.735 inches and 2.765 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+69.0/+96.0 hertz single indicator single range

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 solder lug

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Phase:

Single

Special Features:

100 to 150 vac operation with calibration settings of 50 hz at 75 and 60 hz at 90

Special Markings:

Calibration setting 90 equals 60 cycles, 75 equals 50 cycles

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0