

View Online at <https://aerobasegroup.com/nsn/6625-00-815-0423>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

Between 2.860 inches and 2.890 inches

**Mounting Hole Diameter:**

Between 0.141 inches and 0.171 inches

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

Between 2.485 inches and 2.515 inches

**Mounting Bolt Circle Diameter:**

Between 3.172 inches and 3.202 inches

**Furnished Items And Quantity:**

Mtg hdw 3

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+50.000/+60.000 hertz

**Resonant Reed Quantity:**

14

**Meter Depth Behind Mounting Flange:**

2.000 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 2.735 inches and 2.765 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Measurement Range:**

+69.0/+96.0 hertz single indicator single range

**Scale Selection Method:**

Terminal

**Circuit Attachment Method And Quantity:**

2 solder lug

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 130.0 ac

**Phase:**

Single

**Special Features:**

100 to 150 vac operation with calibration settings of 50 hz at 75 and 60 hz at 90

**Special Markings:**

Calibration setting 90 equals 60 cycles, 75 equals 50 cycles

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0