

View Online at <https://aerobasegroup.com/nsn/6625-00-815-2563>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.070 inches

**Mounting Hole Diameter:**

0.138 inches

**Scale Division Quantity:**

25 single indicator 2nd range

**Overall Diameter:**

3.500 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Nut 3; washer 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

50.0 microamperes

**Dial Scale Marking Color:**

White single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.410 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator all ranges

**Pointer Color:**

White single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator 1st range

**Measurement Range:**

+0.0/+500.0 hertz single indicator 1st range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and shatterproof glass and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 screw and 2 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

Sealed do not open, plus sign and ruggedized on back of meter

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0