

View Online at <https://aerobasegroup.com/nsn/6625-00-816-3768>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Scale Division Quantity:

11 single indicator single range

Overall Diameter:

3.510 inches

Environmental Protection:

Dust resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg screws nuts lockwashers 4, terminal @nuts washers 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

150.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-20.0/+20.0 microamperes, dc single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

Caption microamperes d. C. Center of dial below div scale

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-10304/12 government specification

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0