NSN 6625-00-819-5911

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-819-5911

	,
(Overall Length:
	17.000 inches
(Overall Height:
	10.000 inches
(Overall Width:
(6.750 inches
	Current Type:
,	Ac
I	Frequency Rating:
(60.0 hertz
,	Voltage Rating:
E	Between 105.0 volts and 125.0 volts
I	Beam Quantity:
	1
I	Mounting Method:
I	Portable
;	Screen Size:
:	3 in.
;	Sweep Circuits:
I	Included
(Generator Driven Feature:
I	Not included
;	Sweep Frequency Range:
-	+50.000/+800.000 hertz
;	Single Trigger Sweep Duration:
ę	90.0 microseconds
-	Trigger Sweep Voltage Amplitude Rating:
	150.0 volts
-	Trigger Sweep Polarity Switch:
I	Included
I	Expanded Sweep:
I	Not provided
1	Amplifier Deflection Sensitivity Provision:
I	Provided
1	Vertical Deflection Sensitivity Voltage Rating:
(0.1 volts rms per inch and 50.0 volts rms per inch
I	Horizontal Deflection Sensitivity Voltage Rating:
(0.5 volts cw outside diameter and 500.0 volts peak outside diameter
	Input Intensity Modulation Feature:
	Not provided
I	Plate Direct Connection Deflection Sensitivity Provision:
1	Not provided

NSN 6625-00-819-5911

Oscilloscope - Page 2 of 2



Frequency Response Rating:
Provided
Y-axis Frequency Response Rating:
Between 2.0 hertz and 3500000.0 hertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
10.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Special Features:
X-axis frequency response rating: dc to 4 mc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

T320-g