

View Online at <https://aerobasegroup.com/nsn/6625-00-820-8459>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

20 single indicator all ranges

Environmental Protection:

Dustproof

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

0.875 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+2.0 amperes, dc single indicator 2nd range

Scale Selection Method:

Terminal

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solderless lug

Special Features:

Linear scale

Special Markings:

Caption d.C. Amps center of dial below div scale

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0