

View Online at <https://aerobasegroup.com/nsn/6625-00-820-8461>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.523 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.306 inches and 1.318 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.306 inches and 1.318 inches

Overall Height:

1.625 inches

Overall Width:

1.625 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

20 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.280 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Decrease; 5; 4; 3; 2; 1; 0; increase; 1; 2; 3; 4; 5

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Special Markings:

Extended zero ctr line

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Supplementary Features:

1 pct dc resistance tolerance

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0