

View Online at <https://aerobasegroup.com/nsn/6625-00-821-8616>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Reliability Indicator:

Not established

Overall Length:

2.670 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

100 single indicator single range

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Screw 3, nut 3, lockwasher 3, gasket 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Background Color:

Black single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+100.0 milliamperes, dc single indicator single range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 solderless lug

Special Features:

Linear scale

Special Markings:

Caption milliamperes d. C. Center of dial below div scale, cross hatch area from 25 to 60 ma and from 65 to 85 ma

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0