

View Online at <https://aerobasegroup.com/nsn/6625-00-824-1488>

Circuit Current For Which Designed:

Dc

Overall Length:

2.530 inches

Mounting Hole Diameter:

0.140 inches

Scale Division Quantity:

40 single indicator single range

Overall Diameter:

2.590 inches

Environmental Protection:

Dripproof

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Gasket 1; nut 7; lockwasher 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.390 inches

Meter Body Diameter Behind Mounting Flange:

2.050 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

100; 0; +100

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

Deviation

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0