## NSN 6625-00-824-1488

Arbitrary Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-824-1488

Circuit Current For Which Designed:  Dc  Overall Length: 2.530 inches  Mounting Hole Diameter: 0.140 inches  Scale Division Quantity: 40 single indicator single range  Overall Diameter: 2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter: 2.440 inches  Furnished Items And Quantity: Gasket 1; nut 7; lockwasher 5  Indicator Type: Dial w/pointer  Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle  Sensitivity Rating: 50.0 microamperes  Dial Scale Marking Color:
Overall Length:  2.530 inches  Mounting Hole Diameter:  0.140 inches  Scale Division Quantity:  40 single indicator single range  Overall Diameter:  2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter:  2.440 inches  Furnished Items And Quantity:  Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
Mounting Hole Diameter:  0.140 inches  Scale Division Quantity: 40 single indicator single range  Overall Diameter: 2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter: 2.440 inches  Furnished Items And Quantity: Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design: Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating: 50.0 microamperes
Mounting Hole Diameter:  0.140 inches  Scale Division Quantity:  40 single indicator single range  Overall Diameter:  2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter:  2.440 inches  Furnished Items And Quantity:  Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
O.140 inches  Scale Division Quantity:  40 single indicator single range  Overall Diameter:  2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter:  2.440 inches  Furnished Items And Quantity:  Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
Scale Division Quantity:  40 single indicator single range  Overall Diameter:  2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter:  2.440 inches  Furnished Items And Quantity:  Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
40 single indicator single range  Overall Diameter: 2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter: 2.440 inches  Furnished Items And Quantity: Gasket 1; nut 7; lockwasher 5  Indicator Type: Dial w/pointer Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle  Sensitivity Rating: 50.0 microamperes
Overall Diameter:  2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter:  2.440 inches  Furnished Items And Quantity:  Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
2.590 inches  Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter:  2.440 inches  Furnished Items And Quantity:  Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
Environmental Protection:  Dripproof  Mounting Bolt Circle Diameter: 2.440 inches  Furnished Items And Quantity: Gasket 1; nut 7; lockwasher 5 Indicator Type: Dial w/pointer Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle  Sensitivity Rating: 50.0 microamperes
Dripproof  Mounting Bolt Circle Diameter: 2.440 inches  Furnished Items And Quantity: Gasket 1; nut 7; lockwasher 5 Indicator Type: Dial w/pointer Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle  Sensitivity Rating: 50.0 microamperes
Mounting Bolt Circle Diameter:  2.440 inches  Furnished Items And Quantity:  Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
2.440 inches  Furnished Items And Quantity:  Gasket 1; nut 7; lockwasher 5  Indicator Type:  Dial w/pointer  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
Furnished Items And Quantity: Gasket 1; nut 7; lockwasher 5 Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 microamperes
Gasket 1; nut 7; lockwasher 5 Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 microamperes
Indicator Type: Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 microamperes
Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 microamperes
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 microamperes
Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 microamperes
Three hole/stud bolt circle  Sensitivity Rating:  50.0 microamperes
Sensitivity Rating: 50.0 microamperes
50.0 microamperes
·
Dial Scale Marking Color:
Diai ocale Marking Color.
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.390 inches
Meter Body Diameter Behind Mounting Flange:
2.050 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Scale Marking:
100; 0; +100

## NSN 6625-00-824-1488

Arbitrary Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
<b>Circuit Attachment Method And Quantity:</b>
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Special Markings:
Deviation
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Special Test Features:
Complies with mil-m-10304
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0