

View Online at <https://aerobasegroup.com/nsn/6625-00-825-3146>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.310 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Nut 3; lock washer 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.750 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0/+150.0 volts, ac single indicator single range

**Features Provided:**

Nonglare glass and zero adjuster

**Circuit Attachment Method And Quantity:**

2 screw and 2 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

Green line 115 mark, length of line 0.25 in.

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-m-10304, type mr26w150acvvr

**Style Designator:**

Round flush mtg

**Supplementary Features:**

External resistor may be mounted on back of meter

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0