

View Online at <https://aerobasegroup.com/nsn/6625-00-827-6807>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.297 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.729 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.298 inches

**Overall Height:**

3.375 inches

**Scale Division Quantity:**

28 single indicator single range

**Mounting Stud Length:**

0.228 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.364 inches

**Furnished Items And Quantity:**

Nut 7; washer 7

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud triangular

**Sensitivity Rating:**

500.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.923 inches

**Meter Body Diameter Behind Mounting Flange:**

2.668 inches

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+140.0 kilowatts single indicator single range

**Mounting Stud Diameter:**

0.124 inches

**Features Provided:**

Knife edge pointer and zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Pos terminal marked with a + sign

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Chromate

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, electronic equipdment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0