

View Online at <https://aerobasegroup.com/nsn/6625-00-827-6807>

Circuit Current For Which Designed:

Dc

Overall Length:

2.297 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.729 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.298 inches

Overall Height:

3.375 inches

Scale Division Quantity:

28 single indicator single range

Mounting Stud Length:

0.228 inches

Shortest Horizontal Distance Between Mounting Centers:

1.364 inches

Furnished Items And Quantity:

Nut 7; washer 7

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.923 inches

Meter Body Diameter Behind Mounting Flange:

2.668 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+140.0 kilowatts single indicator single range

Mounting Stud Diameter:

0.124 inches

Features Provided:

Knife edge pointer and zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Pos terminal marked with a + sign

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipdment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0