

View Online at <https://aerobasegroup.com/nsn/6625-00-830-4467>

Circuit Current For Which Designed:

Ac

Reliability Indicator:

Not established

Overall Length:

1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches

Overall Height:

4.000 inches

Overall Width:

4.660 inches

Mounting Stud Length:

0.500 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

1 flange and 4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-10.0/+10.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Switch

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Special Markings:

Red line at plus 5 v

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

FiiG:

A310a0