

View Online at <https://aerobasegroup.com/nsn/6625-00-832-2975>

**Circuit Current For Which Designed:**

Ac

**Reliability Indicator:**

Not established

**Overall Length:**

1.600 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.560 inches

**Overall Height:**

4.200 inches

**Overall Width:**

4.660 inches

**Scale Division Quantity:**

60 single indicator single range

**Mounting Stud Length:**

0.650 inches

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+0.020/+2.000 kilohertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-5.0/+5.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

2.750 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded stud

**Measurement Range:**

+100.0/+130.0 volts, ac single indicator single range

**Mounting Stud Diameter:**

0.138 inches

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Also designed for nonmagnetic panel

**Material:**

Plastic phenolic

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0