NSN 6625-00-833-0391

Arbitrary Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-833-0391
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.850 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
50 single indicator single range
Overall Diameter:
3.510 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Mtg hdw 6; term. Hdw 8
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:

Pointer Color:

Black single indicator single range

White single indicator single range

NSN 6625-00-833-0391

Arbitrary Scale Meter - Page 2 of 2



Scale Marking: 0; 20; 40; 60; 80; 100 **Mounting Facility Type And Quantity:** 3 screw and 3 unthreaded hole **Scale Graduation Type:** Linear single indicator single range **Features Provided:** Luminous scale marking and magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 solder lug and 2 threaded stud **Special Features:** Ruggedized **Special Markings:** Red line center scale Material: Stainless steel **Nuclear Hardness Critical Feature:** Nonhardened **Surface Treatment: Enamel semigloss Special Test Features:** Conforms to milspec mil-m-10304 **Surface Treatment Specification:** Mil-f-14072 military specification single treatment response Style Designator: Round flush mtg **Supplementary Features:** CI res-1000 10 ohms response time-3 seconds **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A310a0 Mil-std (military Standard):

Mil-f-14072 spec.