Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.719 inches

Mounting Hole Diameter:

0.160 inches

Scale Division Quantity:

8 single indicator single range

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

2.781 inches

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+56.000/+64.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

9

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.500 inches

Meter Body Diameter Behind Mounting Flange:

2.687 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+56.0/+64.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0