

View Online at <https://aerobasegroup.com/nsn/6625-00-834-1150>

Circuit Current For Which Designed:

Dc

Overall Length:

2.191 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Overall Height:

4.531 inches

Overall Width:

6.031 inches

Scale Division Quantity:

60 single indicator 1st range

Mounting Stud Length:

0.380 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

250.0 millivolts

Dial Scale Marking Color:

Black all indicators single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.580 inches

Meter Body Diameter Behind Mounting Flange:

2.688 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White all indicators single range

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

-3.0/+3.0 milliamperes, dc single indicator 1st range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Switch

Features Provided:

Self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

Neg sign and pos sign at respective sides of scale

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0