

View Online at <https://aerobasegroup.com/nsn/6625-00-834-9359>

Circuit Current For Which Designed:

Ac

Overall Length:

2.244 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.604 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.294 inches

Overall Height:

3.947 inches

Overall Width:

4.256 inches

Mounting Hole Diameter:

0.140 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 6; lockwasher 5; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.110 inches

Meter Body Diameter Behind Mounting Flange:

3.226 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+3.0/+10.0 volts, standing wave ratio single indicator 5th range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

On bottom of scale, square law detector

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0