NSN 6625-00-834-9359

Multimeter - Page 1 of 2

External



View Online at https://aerobasegroup.com/nsn/6625-00-834-9359

Circuit Current For Which Designed:
Ac
Overall Length:
2.244 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.604 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.294 inches
Overall Height:
3.947 inches
Overall Width:
4.256 inches
Mounting Hole Diameter:
0.140 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Nut 6; lockwasher 5; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 microamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.110 inches
Meter Body Diameter Behind Mounting Flange:
3.226 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:

NSN 6625-00-834-9359Multimeter - Page 2 of 2



Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator all ranges
Measurement Range:
+3.0/+10.0 volts, standing wave ratio single indicator 5th range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
On bottom of scale, square law detector
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0