## NSN 6625-00-835-7028

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-835-7028

| Circuit Current For Which Designed:                         |
|---|
| Dc  |
| Overall Length:   |
| 2.850 inches  |
| Mounting Hole Diameter:                                     |
| 0.150 inches  |
| Overall Diameter:   |
| 3.510 inches  |
| Mounting Bolt Circle Diameter:                              |
| 3.160 inches  |
| Installation Design:  |
| Panel   |
| Mounting Arrangement Style:                                 |
| Three hole/stud bolt circle                                 |
| Sensitivity Rating:   |
| 50.0 microamperes   |
| Dial Scale Marking Color:                                   |
| Black single indicator single range                         |
| Accuracy In Percent:  |
| -2.0/+2.0 at full scale single indicator single range       |
| Meter Depth Behind Mounting Flange:                         |
| 2.450 inches  |
| Meter Body Diameter Behind Mounting Flange:                 |
| 2.800 inches  |
| Movement Type:  |
| Moving coil, permanent magnet                               |
| Background Color:   |
| White single indicator single range                         |
| Mounting Facility Type And Quantity:                        |
| 3 unthreaded hole   |
| Circuit Attachment Method And Quantity:                     |
| 2 solder lug  |
| Special Features:   |
| Scale is without numerals or letters                        |
| Special Markings:   |
| Green area from 0.0 to 20.4ua calibration, vswr under scale |
| Nuclear Hardness Critical Feature:                          |
| Nonhardened   |
| Style Designator:   |
| Round flush mtg   |
| Shelf Life:   |
|   |

N/a

## NSN 6625-00-835-7028

Special Scale Meter - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A310a0