NSN 6625-00-836-2294

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-836-2294

Overall Length:
21.250 inches
Overall Height:
15.000 inches
Overall Width:
9.750 inches
Current Type:
Ac
Frequency Rating:
50.0 hertz
Voltage Rating:
Between 115.0 volts and 230.0 volts
Beam Quantity:
1
Screen Size:
5.000 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Single Trigger Sweep Duration:
Between 0.2 seconds and 5.0 seconds
Trigger Sweep Voltage Amplitude Rating:
50.0 volts
Trigger Sweep Polarity Switch:
Not included
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
2.6 kilovolts rms per inch
Horizontal Deflection Sensitivity Voltage Rating:
26.0 kilovolts rms per inch
Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Provided
Direct Connection Vertical Deflection Sensitivity Voltage Rating:
35.8 volts any acceptable outside diameter
Direct Connection Horizontal Deflection Sensitivity Voltage Rating

35.8 volts any acceptable outside diameter

NSN 6625-00-836-2294

Oscilloscope - Page 2 of 2



Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
Between 0.0 kilohertz and 300.0 kilohertz
Y-axis Frequency Response Rating:
Between 0.0 kilohertz and 300.0 kilohertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
2.0 megohms
Y-axis Input Impedance Rating:
2.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Fsc Application Data:
Oscilloscope, except specially designed
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
T320-g