

View Online at <https://aerobasegroup.com/nsn/6625-00-837-3264>

Circuit Current For Which Designed:

Dc

Overall Length:

1.983 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

3.510 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 3; washer 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range and green single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or

Meter Depth Behind Mounting Flange:

1.063 inches

Meter Body Diameter Behind Mounting Flange:

2.680 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Volts direct current

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Special Markings:

Black indi line at 0.6 ma with green on ea side

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Special Test Features:

Conforms to mil-m-10304/12 type mr36w001dcmar

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0