

View Online at <https://aerobasegroup.com/nsn/6625-00-838-0148>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.306 inches and 1.318 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.306 inches and 1.318 inches

Overall Height:

Between 1.734 inches and 1.805 inches

Overall Width:

Between 1.734 inches and 1.805 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

25 single indicator single range

Environmental Protection:

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

End Application:

5840-00-004-9282 radar set

Furnished Items And Quantity:

Nut 4; lockwasher 4; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+1.0 amperes, dc single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Special Markings:

0, .2, .4, .6, .8, 1

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Electrical, electronic properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0