

View Online at <https://aerobasegroup.com/nsn/6625-00-840-0365>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2500.0

Overall Length:

1.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.240 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.240 inches

Overall Height:

3.250 inches

Overall Width:

3.250 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.375 inches

Environmental Protection:

Dust resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.080 inches

Meter Body Diameter Behind Mounting Flange:

2.730 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+5.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel lusterless

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0