

View Online at <https://aerobasegroup.com/nsn/6625-00-840-5690>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

5000.0

Overall Length:

6.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.375 inches

Overall Height:

6.880 inches

Overall Width:

6.630 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

0.760 inches

Furnished Items And Quantity:

Lockwasher 6, nut 12, shunt 1, washer 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.520 inches

Meter Body Width Behind Mounting Flange:

5.750 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+30.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.164 inches

Meter Body Height Behind Mounting Flange:

6.000 inches

Features Provided:

Magnetic shield and portable

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Amperes d.C., Ip, Ip, plus symbol

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular semi-flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0