

View Online at <https://aerobasegroup.com/nsn/6625-00-841-6641>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

Between 2.944 inches and 3.004 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

Between 3.480 inches and 3.520 inches

Environmental Protection:

Waterproof

Mounting Bolt Circle Diameter:

Between 3.150 inches and 3.170 inches

Furnished Items And Quantity:

Nut 3; washer 3

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Resonant Reed Quantity:

5

Meter Depth Behind Mounting Flange:

Between 2.230 inches and 2.270 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.670 inches and 2.710 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Measurement Range:

+58.0/+62.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Reeds have high q characteristics

Material:

Plastic phenol-formaldehyde

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Supplementary Features:

Temp compensations not required

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0