

View Online at <https://aerobasegroup.com/nsn/6625-00-841-6641>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

Between 2.944 inches and 3.004 inches

**Mounting Hole Diameter:**

0.150 inches

**Overall Diameter:**

Between 3.480 inches and 3.520 inches

**Environmental Protection:**

Waterproof

**Mounting Bolt Circle Diameter:**

Between 3.150 inches and 3.170 inches

**Furnished Items And Quantity:**

Nut 3; washer 3

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Resonant Reed Quantity:**

5

**Meter Depth Behind Mounting Flange:**

Between 2.230 inches and 2.270 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 2.670 inches and 2.710 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Measurement Range:**

+58.0/+62.0 hertz single indicator single range

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Reeds have high q characteristics

**Material:**

Plastic phenol-formaldehyde

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Temp compensations not required

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0