

View Online at <https://aerobasegroup.com/nsn/6625-00-842-0897>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.969 inches

**Mounting Hole Diameter:**

0.150 inches

**Overall Diameter:**

3.500 inches

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Nut 3; washer 3; face plate cover 1

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

2

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator all ranges

**Resonant Reed Quantity:**

10

**Accuracy In Percent:**

-0.3/+0.3 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

2.250 inches

**Meter Body Diameter Behind Mounting Flange:**

2.688 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Measurement Range:**

+58.0/+62.0 hertz single indicator 2nd range

**Scale Selection Method:**

Terminal

**Circuit Attachment Method And Quantity:**

2 solder lug

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 130.0 ac

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0