## NSN 6625-00-844-3691

Voltmeter - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/6625-00-844-3691

| Circuit Current For Which Designed:  |
|--|
| Dc   |
| Dielectric Withstanding Voltage In Volts:  |
| 3000.0   |
| Overall Length:  |
| 2.850 inches   |
| Scale Division Quantity:   |
| 50 single indicator single range   |
| Mounting Stud Length:  |
| 0.500 inches   |
| Overall Diameter:  |
| 3.510 inches   |
| Environmental Protection:  |
| Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight |
| Mounting Bolt Circle Diameter:   |
| 3.160 inches   |
| Furnished Items And Quantity:  |
| Mtg hdw 3  |
| Indicator Type:  |
| Dial w/pointer   |
| Installation Design:   |
| Panel  |
| Mounting Arrangement Style:  |
| Three hole/stud bolt circle  |
| Sensitivity Rating:  |
| 1.0 milliamperes   |
| Dial Scale Marking Color:  |
| White single indicator single range  |
| Accuracy In Percent:   |
| -2.0/+2.0 at full scale single indicator single range  |
| Unable To Decode:  |
| Unable to decode or unable to decode   |
| Meter Depth Behind Mounting Flange:  |
| 2.450 inches   |
| Meter Body Diameter Behind Mounting Flange:  |
| 2.800 inches   |
| Movement Type:   |
| Moving iron vane   |
| Background Color:  |
| Black single indicator single range  |

Pointer Color:

White single indicator single range

## **NSN 6625-00-844-3691** Voltmeter - Page 2 of 3

Fiig:



| Power Source:  |
|--|
| External   |
| Mounting Facility Type And Quantity:   |
| 3 threaded stud  |
| Scale Graduation Type:   |
| Linear single indicator single range   |
| Measurement Range:   |
| +0.0/+100.0 volts, dc single indicator single range  |
| Mounting Stud Diameter:  |
| 0.138 inches   |
| Scale Selection Method:  |
| Terminal   |
| Features Provided:   |
| Luminous scale marking and magnetic shield and zero adjuster   |
| Movement Suspension Method:  |
| Jewel pivot base   |
| Circuit Attachment Method And Quantity:  |
| 2 threaded stud and 2 solder lug   |
| Special Features:  |
| Ruggedized   |
| Material:  |
| Steel  |
| Nuclear Hardness Critical Feature:   |
| Nonhardened  |
| Surface Treatment:   |
| Enamel semigloss   |
| Surface Treatment Specification:   |
| Mil-f-14072 military specification single treatment response   |
| Style Designator:  |
| Round flush mtg  |
| Test Data Document:  |
| 81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-m-10304/11 government specification  |
| Fsc Application Data:  |
| Test set, elect. Equip.  |
| Shelf Life:  |
|  |
| N/a Unit Of Measure:   |
| Unit Of Measure:   |
| Domilitarination   |
| Demilitarization:  |
| No   |

## NSN 6625-00-844-3691

Voltmeter - Page 3 of 3



Mil-std (military Standard):

Mil-f-14072 spec.