

View Online at <https://aerobasegroup.com/nsn/6625-00-846-5265>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.283 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.540 inches

**Overall Height:**

4.596 inches

**Overall Width:**

4.147 inches

**Scale Division Quantity:**

30 single indicator single range

**Mounting Stud Length:**

0.625 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:**

Nut 8; lockwasher 6; seal 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

50.0 millivolts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

2.710 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+1.5 amperes, dc single indicator single range

**Mounting Stud Diameter:**

0.132 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized; sealed

**Material:**

Plastic phenolic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0