

View Online at <https://aerobasegroup.com/nsn/6625-00-849-1192>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

Between 5.281 inches and 5.343 inches

**Mounting Hole Diameter:**

0.156 inches

**Scale Division Quantity:**

40 single indicator single range

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

3.500 inches

**Environmental Protection:**

Dust resistant

**Mounting Bolt Circle Diameter:**

3.156 inches

**Furnished Items And Quantity:**

Mtg screws, nuts, and lockwashers 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+55.000/+550.000 hertz

**Dial Scale Marking Color:**

Green, phosphorescent single indicator single range

**Accuracy In Percent:**

-0.6/+0.6 at 1/2 scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.718 inches

**Meter Body Diameter Behind Mounting Flange:**

2.672 inches

**Movement Type:**

Moving iron vane

**Background Color:**

Black single indicator single range

**Pointer Color:**

Yellow, fluorescent single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+105.0/+550.0 volts, ac single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 binding post

**Phase:**

Single

**Special Markings:**

Volts ac on face of dial scale

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0