

View Online at <https://aerobasegroup.com/nsn/6625-00-849-1192>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

Between 5.281 inches and 5.343 inches

Mounting Hole Diameter:

0.156 inches

Scale Division Quantity:

40 single indicator single range

Frequency Rating:

60.0 hertz

Overall Diameter:

3.500 inches

Environmental Protection:

Dust resistant

Mounting Bolt Circle Diameter:

3.156 inches

Furnished Items And Quantity:

Mtg screws, nuts, and lockwashers 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+55.000/+550.000 hertz

Dial Scale Marking Color:

Green, phosphorescent single indicator single range

Accuracy In Percent:

-0.6/+0.6 at 1/2 scale single indicator single range

Meter Depth Behind Mounting Flange:

3.718 inches

Meter Body Diameter Behind Mounting Flange:

2.672 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator single range

Pointer Color:

Yellow, fluorescent single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+105.0/+550.0 volts, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Phase:

Single

Special Markings:

Volts ac on face of dial scale

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0