NSN 6625-00-850-1920

Voltmeter - Page 1 of 2

Dc

Overall Length: 2.350 inches Overall Height:

0.112 inches

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-850-1920

| 2.690 inches |
|---|
| Overall Width: |
| 2.690 inches |
| Scale Division Quantity: |
| 10 single indicator single range |
| Mounting Stud Length: |
| 0.500 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.180 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.150 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+1.0 volts, dc single indicator single range |
| Mounting Stud Diameter: |

NSN 6625-00-850-1920

Voltmeter - Page 2 of 2



| Features Provided: |
|---|
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set electronic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |