

View Online at <https://aerobasegroup.com/nsn/6625-00-851-3626>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

11.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Overall Height:

Between 4.250 inches and 4.750 inches

Overall Width:

Between 4.250 inches and 4.750 inches

Scale Division Quantity:

30 single indicator single range

Frequency Rating:

400.0 hertz

Mounting Stud Length:

0.625 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant and submersible and vibration resistant and watertight

Furnished Items And Quantity:

Mtg hdw 4; terminal hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+360.000/+440.000 hertz

Sensitivity Rating:

10.0 volt-amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

10.000 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+150.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Terminal

Features Provided:

Luminous scale marking and magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Phase:

Single

Material:

Plastic

Material Specification:

Mil-p-14 military specification all material responses

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Test Data Document:

81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A310a0

Mil-std (military Standard):

Mil-p-14 spec.