NSN 6625-00-851-9666

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-851-9666

Mounting Hole Diameter: 0.156 inches Scale Division Quantity: 50 single indicator single range Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Scale Division Quantity: 50 single indicator single range Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Scale Division Quantity: 50 single indicator single range Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
3.500 inches Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Three hole/stud bolt circle Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Accuracy In Percent: -1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
-1.0/+1.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Meter Depth Behind Mounting Flange: 1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
1.719 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:							
2.750 inches Movement Type:							
Movement Type:							
Marriage and the second second							
Moving coil, permanent magnet							
Background Color:							
White single indicator single range							
Mounting Facility Type And Quantity:							
3 unthreaded hole							
Measurement Range:							
+0.0/+50.0 volts, dc single indicator single range							
Movement Suspension Method:							
Jewel pivot base							
Circuit Attachment Method And Quantity:							
2 solder lug							
Special Features:							
Nonglare glass							
Style Designator:							
C1 round flush mtg							
Shelf Life:							
N/a							

NSN 6625-00-851-9666

Voltmeter - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A310a0