## NSN 6625-00-855-1023

Voltmeter - Page 1 of 2

**Pointer Color:** 

Black single indicator all ranges



View Online at https://aerobasegroup.com/nsn/6625-00-855-1023

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.480 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.977 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.535 inches
Overall Height:
4.194 inches
Overall Width:
4.664 inches
Scale Division Quantity:
100 single indicator 2nd range
Mounting Stud Length:
0.503 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 8; lockwasher 4; flat washer 4; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.143 inches
Meter Body Diameter Behind Mounting Flange:
2.734 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator all ranges

## NSN 6625-00-855-1023

Voltmeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
-500.0/+500.0 volts, dc single indicator 2nd range
Mounting Stud Diameter:
0.134 inches
Scale Selection Method:
Terminal
Features Provided:
Magnetic shield and mirror scale and zero adjuster
<b>Movement Suspension Method:</b>
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On back, sealed do not open
Material:
Plastic phenolic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0