

View Online at <https://aerobasegroup.com/nsn/6625-00-856-4379>

Circuit Current For Which Designed:

Dc

Overall Length:

1.218 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Scale Division Quantity:

21 single indicator single range

Furnished Items And Quantity:

Thd mtg ring 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.720 inches

Meter Body Diameter Behind Mounting Flange:

1.406 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 flange and 1 threaded body

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-10.0/+10.0 milliamperes, dc single indicator single range

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Meter sealed, linear scale

Special Markings:

Caption milliamperes direct current @located center of dial below div scale and rh terminal marked pos and lh terminal marked neg

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Shock iaw mil-s-901b; vibration iaw mil-std-167

Style Designator:

Fan shape flush mtg

Supplementary Features:

Res 9, 900 porm 1 pct at 25 degrees centigrade

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0