

View Online at <https://aerobasegroup.com/nsn/6625-00-857-3030>

Circuit Current For Which Designed:

Ac

Overall Length:

2.180 inches

Overall Height:

3.500 inches

Overall Width:

3.500 inches

Scale Division Quantity:

10 single indicator single range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 2; washer 2

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

11

Meter Depth Behind Mounting Flange:

1.821 inches

Meter Body Diameter Behind Mounting Flange:

2.000 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+57.5/+62.5 hertz single indicator single range

Mounting Stud Diameter:

0.138 inches

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

120.0 ac

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0