NSN 6625-00-857-4352

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-857-4352

| Mounting Type: |
|---|
| Case |
| Overall Length: |
| 21.000 inches |
| Overall Height: |
| 16.750 inches |
| Overall Width: |
| 13.250 inches |
| Current Type: |
| Ac |
| Frequency Rating: |
| Between 50.0 hertz and 400.0 hertz |
| Case Material: |
| Aluminum |
| Case Surface Treatment: |
| Enameled |
| Frequency Range Rating: |
| +10.000/+480.000 megahertz |
| Internal Battery Accommodation: |
| Not included |
| Output Impedance Rating: |
| 50.0 ohms |
| Voltage Rating: |
| Between 115.0 volts and 230.0 volts |
| Frequency Band Quantity: |
| 5 |
| Modulation Type: |
| Am |
| Calibration Accuracy Rating: |
| Porm 0.5 pct accuracy of calibration |
| Crystal Controlled Feature: |
| Provided |
| Calibrated Signal Output Range: |
| 0.1 uv to 1v, calibrated output |
| Maximum Signal Output: |
| Specified in bhfz |
| Signal Output Constancy: |
| Porm 1 db maximum variation throughout freq range |
| Modulator Location: |
| External |
| Modulated Frequency Rating: |
| Between 0.020 kilohertz and 20.0 kilohertz |

NSN 6625-00-857-4352

Signal Generator - Page 2 of 2



| Modulation Degree: |
|--------------------------------------|
| Between 0.0 percent and 95.0 percent |
| Phase: |
| Single |
| Functional Classification: |
| Bb-1.1 |
| Entry Date: |
| 91-02-12 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: T320-j