

View Online at <https://aerobasegroup.com/nsn/6625-00-858-4583>

**Circuit Current For Which Designed:**

Ac

**Overall Diameter:**

Between 1.993 inches and 2.000 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

0.5 amperes

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

Between 2.287 inches and 2.307 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 1.923 inches and 1.937 inches

**Movement Type:**

Moving iron vane

**Scale Marking:**

De-icer empennage; ok; faulty

**Mounting Facility Type And Quantity:**

1 clamp

**Scale Graduation Type:**

Nonlinear single indicator single range

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

1 connector, receptacle

**Special Markings:**

Ok band from 0 to .36 amp deflection; faulty band from .36 to .5

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0